## **CHECKLIST FOR CORNER DOCUMENTS**

(Filed with the MDA Land Survey Program)

<del></del>		<b>DATE OF</b> 1	DATE OF FORM: DATE:			
		DATE:				
CORNER LOCATION: TOWNSHIP: RANGE: _			INDEX NO			
<u>AL</u>	L CORNER DOCUMENTS SHALL SHOW	THE FOLLOWING:	YES	<u>NO</u>	<u>NA</u>	
1)	Check box for restoration, establishment or reestablishment					
2)	Lettering or typing not less than 0.08" in height					
3)	Lettering or typing in black ink					
<b>4</b> )	Drawings clear and sharp					
5)	Description of original monument and accessories					
6)	Description of any subsequent surveys					
7)	Surveyor's seal with date and signature on	front and back sheet				
8)	Date of survey field work					
9)	Basis of bearing system used					
10)	Description of existing or reestablished mon	nument and accessorie	s			
11)	Comprehensive sketch of corner location (re	eference ties)				
12)	Sketch is in accordance with MO CSR 2 90-	-61.080				
13)	State coordinates, if known					

1 06/27/17

RESTORATION OR ALTERATION OF EXISTING MONUMENT:		<u>NO</u>	<u>NA</u>
13) Description of evidence found and used in restoration			
14) Resident witness affidavits			
15) Distance and direction used in restoration			
FOR REESTABLISHED MONUMENTS:			
16) Statement of method used to reestablish corner.			
17) Distances and directions used in the reestablishment procedure.			
WHEN COORDINATES ARE SHOWN:			
18) Coordinates of corner in meters			
19) Relative positional tolerance of coordinates obtained for corner monument			
20) Zone of corner coordinates			
21) Project grid factor used			
22) Coordinates of 1 <sup>st</sup> and 2 <sup>nd</sup> Order Control Station used			
23) Control station coordinate origin (agency)			
24) Coordinates of control station(s)			
25) Date of adjustment or epoch date, of control station(s)			
26) Zone of control station(s)			
27) Brief statement of the method used to obtain the position			

2 06/27/17